

Acrylate Leveling agents			
Product name	Active	Solvent	Application
<u>Tilo-L8510</u>	52%	Xyl	It has extensive compatibility, no turbidity in varnish. It is widely used for solvent-based coating system and printing inks, particularly suitable for thick film varnish.
<u>Tilo-L8511</u>	52%	Xyl	It has extensive compatibility, no turbidity in varnish and no haze in color paint. It is widely used for solvent-based coating system and printing inks.
<u>Tilo-L8512</u>	> 95%	----	It is a polyacrylate surface auxiliary used as medium polarity solvent-based leveling agent, with extensive compatibility, It is widely used for coating systems, printing inks and power coatings. No turbidity in varnish and no haze in color paint. It is solvent-free Tilo-L8510.
<u>Tilo-L8520</u>	50%	Xyl	It has great compatibility and also provides good leveling with air releasing effect. It can be used for varnish.
<u>Tilo-L8521</u>	50%	Xyl	It has fast leveling with air releasing effect. It is used for medium polarity system. Recommended for coil coatings.
<u>Tilo-L8522</u>	50%	Xyl	It has excellent compatibility and also provides with good leveling with air releasing effect. Recommended for PE primer paints.
<u>Tilo-L8537</u>	70%	Xyl	It has outstanding wetting ability for substrate and resins and great anti-cratering ability. It won't impact the adhesion between the layers and also provides excellent leveling with air releasing.
<u>Tilo-L8538</u>	60%	Xyl	It has outstanding wetting ability for substrate and resins and great anti-cratering ability. It won't impact the adhesion between the layers and also provides excellent leveling with air releasing.
<u>Tilo-L8539</u>	70%	PMA	Benzene-free. Outstanding wetting ability for substrate and resins, it has good anti-cratering ability. It won't impact the adhesion between the layers. It provides with excellent leveling with air releasing.
<u>Tilo-L8550</u>	50%	Xyl	It has wide compatibility, no turbidity in varnish and no haze in color paint. It is widely used for solvent-based coating system.
<u>Tilo-L8554</u>	52%	Xyl	A polyacrylate surface additive, it is used for solvent-based coating systems and printing inks. A standard leveling agent with air releasing effect.
<u>TiIO-L8560</u>	50%	PMA	High fluorine content, it has wide compatibility. It is used for fast leveling of large area, low foam stabilization. It has outstanding wetting ability for substrate and resins.
<u>TiIO-L8561</u>	50%	PMA	High fluorine content, with extensive compatibility, it is used for fast leveling of large area, low foam stabilization. It has outstanding wetting ability for substrate and resins. It provides even faster leveling comparing with Tilo-L8560 and balance compatibility in the mean time.
<u>TiIO-L8563</u>	50%	PMA	High fluorine content, with extensive compatibility, it is used for fast leveling of large area, low foam stabilization and it has outstanding wetting ability for substrate and resins. It provides faster leveling and outstanding air-releasing.