

Water based defoamers

Product name	Active	Solvent	Application
<u>Tilo-F2600</u>	100%	----	APEO-free, it is used for water-based color coatings and printing inks. It can effectively prevent generation of microfoam. Especially it is suitable for high gloss and satin systems and also for airless spraying. Medium compatibility, it can be added into paint mixing.
<u>Tilo-F2601</u>	100%	----	APEO-free, it is used for water-based color coatings and printing inks. It can effectively prevent generation of microfoam. Especially it is suitable for high gloss and satin systems and also for airless spraying. Medium compatibility, it can be added into paint mixing.
<u>Tilo-F2602</u>	100%	----	APEO-free, it contains foam-breaking polymer and fumed silica. It is suitable for latex coatings and paste milling.
<u>Tilo-F2631</u>	100%	----	APEO and silicone free, it is used for water-based latex paints and plaster, especially suitable for the system of pigment volume concentration between 35 -70. It is suitable for paste milling.
<u>Tilo-F2632</u>	100%	----	APEO-free, it is used for water-based coating systems, printing inks and paper coatings. It has excellent long-term effects and no negative impact on the color acceptance. It is suitable for paste milling.
<u>Tilo-F2685</u>	100%	----	APEO-free, it is used for water-based color coatings and printing inks. It can effectively prevent generation of microfoam. Especially it is suitable for high gloss and satin systems, and also for airless spraying. Great compatibility, it can be added into paint mixing. Particularly it is suitable for spray coatings and has long-term stability.